

Chimfex

Item 3412

- First line of defense for controlling chimney fires
- Works safely with no water damage
- Fast, toss-in convenience



Description:

A suppressant for chimney fires.

Performance Characteristics (Test results from **Omni Environmental Services**):

- Suppresses a chimney fire in an average of 22 seconds
- Reduces flue temperatures an average of 53% in 2 minutes
- Reduces the oxygen level an average of 43% in 2 minutes
-

Recommended Uses:

Use in wood stoves, fireplaces or fireplace inserts.

Application:

1. Remove the top lid to expose scratch surface on cap.
2. Twist and remove cap to expose black button on Chimfex.
3. Hold away from face and activate by lightly scratching black button with surface of cap.
4. Immediately drop alongside the fire, not directly in the fire.
5. **For Fireplaces:** Close doors or cover opening with non flammable material.
For Wood Stoves: Close doors and all intake vents.
6. Chimfex smoke emissions rise up the flue to replace the oxygen in a few seconds.
7. Due to internal differences in chimneys and wood burning stoves, some large flues may require two or more units activated simultaneously to suppress the fire.

Storage/Handling:

Always point Chimfex away from face and body while activating and afterward. Acquaint your household with use instructions and directions to insure proper and safe handling and use of Chimfex. Store in a cool, dry place.

For disposal: Open burning is preferred method of disposal in compliance with appropriate federal, state and local regulations.

Limitations:

This device is not approved or permissible for use as an alternative for fire extinguishers in any building or motor vehicle where fire extinguishers are required by law, ordinance, or fire marshal regulation.

Warranty and Limited Remedy:

This product will be free from defects in material and manufacture for a period of eighteen (18) months from date of manufacture. Rutland Fire Clay Company makes no other warranties including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose. User is responsible for determining whether the Rutland Fire Clay Company product is fit for a particular purpose and suitable for user's application. If this Rutland Fire Clay Company product is defective within the warranty period stated above, your exclusive remedy and Rutland Fire Clay Company's sole obligation shall be, at Rutland Fire Clay Company's option, to replace the Rutland Fire Clay Company product or refund the

purchase price of the Rutland Fire Clay Company product.

Limitation of Liability:

Except where prohibited by law, Rutland Fire Clay Company will not be liable for any loss or damage arising from this Rutland Fire Clay Company product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

CAUTIONS:

Flammable. Harmful if swallowed. Irritant to eyes, skin and respiratory tract. If swallowed, consult a physician immediately. If eye contact occurs, flush with water for 15 minutes. Consult a physician.

KEEP OUT OF REACH OF CHILDREN